

WALL ADHESIVE

FOR OUTDOOR USE

Tips for Best Results

- Designed for smooth, flat surfaces. Avoid applying over rivets, corrugated surfaces and gaps between two panels.
 - Outdoor adhesive is much easier to apply when wet. Adding a small amount of dish washing soap to a spray bottle filled with water is highly recommended. We suggest a 20:1 water to soap ratio.
 - Items you will need to get started: (1) a spray bottle filled with soapy water solution, (2) a squeegee for smoothing out any air pockets, and (3) a towel for drying
-

Instructions

- 1** Make sure that your poster will fit the space. Measure your wall and your poster.
 - 2** Clean the surface. Use a wet cloth to remove any dust from the wall. If any chemicals are used to clean the wall, be sure to allow enough time for the surface to completely dry before proceeding.
 - 3** Now you're ready to apply the wall adhesive. Begin by spreading out your vinyl poster on a flat surface, face down. Peel the backing off from the top down. For smaller prints, it is ok to peel off the entire backing paper. For larger prints, we recommend you start by peeling only the top 12-24 inches of the backing paper.
 - 4** When you are ready to begin, spray down the surface area with the soapy water solution. Next, generously spray the exposed adhesive on the back side of the poster as well as the front side of the poster. The spray will make the poster more slippery so that the squeegee will perform better. The adhesive backing is pressure sensitive so apply it to the wall lightly at first until you have the poster in position. Once it's in place, you can press more firmly. Smooth out the top of the poster and any air pockets or water trapped underneath by gently working your way from the center out with the squeegee.
 - 5** Slowly peel down the backing paper a few inches at a time. Press the print to the wall and squeegee down from the center out as you work your way down to the bottom of the print. Spray as necessary. Dry any excess water with a towel.
-

Remove and Replace

Carefully remove by starting at one corner. Up to three layers of vinyl can be applied on top of each other as long as the original has been applied for less than six months.